Safety Data Sheet

Firestone Building Products Company

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name

Lap Sealant HS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s)

Construction

1.3 Details of the supplier of the safety data sheet

Manufacturer

• Firestone Building Products Company

250 West 96th Street Indianapolis, IN 46260

United States

firestonemsds@bfdp.com

Telephone (General) • 800-428-4442

1.4 Emergency telephone number

Manufacturer

• (800) 424-9300 - CHEMTREC

Manufacturer

• (703) 527-3887 - CHEMTREC - International

Section 2: Hazards Identification

EU/EEC

According to EU Directive 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010] According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP

• Flammable Liquids 2 - H225 Skin Irritation 2 - H315

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336

Hazardous to the aquatic environment Chronic 2 - H411

DSD/DPD

 Flammable Irritant (Xi)

Harmful (Xn)

Dangerous to the Environment (N)

R11, R38, R67, R51/53

2.2 Label Elements

CLP

DANGER







Hazard statements • H225 - Highly flammable liquid and vapour

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H411 - Toxic to aquatic life with long lasting effects

Precautionary statements

Prevention • P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground and/or bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing dust, fume, gas, mist, vapours and/or spray.

P264 - Wash thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response .

P370+P378 - In case of fire: Use appropriate media for extinction.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 - Call a POISON ČENTER or doctor/physician if you feel unwell.

P303 - IF ON SKIN (or hair):

P353 - Rinse skin with water/shower.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P321 - Specific treatment, see supplemental first aid information.

P362 - Take off contaminated clothing and wash before reuse.

P391 - Collect spillage.

Storage/Disposal • P235 - Keep cool.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P501 - Dispose of content and/or container in accordance with local, regional,

national, and/or international regulations.

DSD/DPD







Risk phrases • R11 - Highly flammable.

R38 - Irritating to skin.

R67 - Vapours may cause drowsiness and dizziness.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases

S9 - Keep container in a well ventilated place

S16 - Keep away from sources of ignition - No Smoking.

S57 - Use appropriate containment to avoid environmental contamination.

2.3 Other Hazards

CLP

According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

DSD/DPD

According to European Directive 1999/45/EC this preparation is considered dangerous.

This product is considered dangerous according to the European Directive 67/548/EEC.

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012

Flammable Liquids 2 - H225 Skin Irritation 2 - H315 Eye Irritation 2 - H319

Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation - H335

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336

2.2 Label elements

OSHA HCS 2012

DANGER





Hazard statements • Highly flammable liquid and vapour - H225 Causes skin irritation - H315

Causes serious eye irritation - H319 May cause respiratory irritation - H335 May cause drowsiness or dizziness - H336

Precautionary statements

Prevention .

Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking. - P210 Keep container tightly closed. - P233

Ground and/or bond container and receiving equipment. - P240 Use explosion-proof electrical/ventilating/lighting/equipment. - P241

Use only non-sparking tools. - P242

Take précautionary measures against static discharge. - P243

Avoid breathing mist/vapours/spray. - P261 Wash thoroughly after handling. - P264

Use only outdoors or in a well-ventilated area. - P271

Wear protective gloves/protective clothing/eye protection/face protection. - P280

Response •

In case of fire: Use appropriate media for extinction. - P370+P378

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. - P304+P340

Call a PŎISON CENTER or doctor/physician if you feel unwell. - P312

IF ON SKIN (or hair): - P303

Rinse skin with water/shower. - P353

If skin irritation occurs: Get medical advice/attention. - P332+P313 Specific treatment, see supplemental first aid information. - P321 Take off contaminated clothing and wash before reuse. - P362

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. - P305+P351+P338 If eye irritation persists: Get medical advice/attention. - P337+P313

Storage/Disposal .

Keep cool. - P235

Store in a well-ventilated place. Keep container tightly closed. - P403+P233

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. - P501

2.3 Other hazards

OSHA HCS 2012

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to WHMIS

2.1 Classification of the substance or mixture

WHMIS

 Flammable Liquids - B2 Other Toxic Effects - D2B

2.2 Label elements

WHMIS





Flammable Liquids - B2 Other Toxic Effects - D2B

2.3 Other hazards WHMIS

 In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

See Section 12 for Ecological Information.

Section 3 - Composition/Information on Ingredients

3.1 Substances

 Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

		Haza	rdous Components		
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments
Limestone	CAS:1317-65-3 EC Number:215- 279-6	30% TO 60%	NDA	EU DSD/DPD: Self Classified - Xn, R48/20 EU CLP: Self Classified - STOT RE 2 (Lung, inhalation) OSHA HCS 2012: STOT RE 2 (Lung, inhalation)	NDA
Light aliphatic solvent naphtha	CAS:64742-89-8 EC Number:265- 192-2 EINECS:265- 192-2	10% TO 30%	NDA	EU DSD/DPD: Self Classified - Xi R38, Xn R67, R65, N; R51/53, F R11 EU CLP: Self Classified - Skin Irrit 2, Asp Tox. 1, STOT SE 3: Narc, Aquatic Chronic 2, Flam Liq. 3 OSHA HCS 2012: Eye Irrit 2; Flam Liq. 2; Skin Irrit. 2; Asp. Tox. 1; STOT Single Exp. 3 narc & resp irritant	NDA
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	CAS:64742-52- 5 EC Number:265- 155-0	< 5%	NDA	EU DSD/DPD: Annex I - Carc.Cat.2; R45 EU CLP: Annex VI - Carc. 1B; H350 OSHA HCS 2012: Skin Irrit. 2	NDA
Bentonite	CAS:1302-78-9 EC Number:215- 108-5	< 1.5%	NDA	EU DSD/DPD: Self Classified - Xn, R48/20 EU CLP: Self Classified - STOT RE 2 (lungs, inhalation) OSHA HCS 2012: STOT RE 2 (lungs, inhalation)	NDA
Carbon Black	CAS:1333-86-4 EC Number:215- 609-9	< 1.5%	Ingestion/Oral-Rat LD50 • >15400 mg/kg Skin-Rabbit LD50 • >3 g/kg	EU DSD/DPD: Self Classified - Xi R37/R38 Carc. 3 EU CLP: Self Classified - STOT SE 3, Skin Irrit 2, Carc Cat 2 OSHA HCS 2012: STOT SE 3, Skin Irrit 2, Carc Cat 2	NDA

Calcium oxide	CAS:1305-78-8 EC Number:215- 138-9 UN:UN1910	< 1%	NDA	EU DSD/DPD: Self Classified - Xi R36/37/38 EU CLP: Self Classified - Skin Irrit 2, H315; Eye Irrit 2, H319; STOT SE 3 H335 OSHA HCS 2012: Skin Irrit 2, Eye Irrit 2, STOT SE 3 (resp)	NDA	
---------------	--	------	-----	--	-----	--

 Limestone, Bentonite and carbon black are not expected to be released from this bonded matrix.

See Section 11 for Toxicological Information.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

 Do not use mouth-to-mouth method if victim inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention if artificial oxygen is administered.

Skin

Eve

 Rinse skin with rubbing alcohol first, followed immediately by washing affected area with soap and water. Remove and isolate contaminated clothing and shoes. Call 911 or emergency medical service.

•

 In case of contact with substance, immediately flush eyes with running water for at least 20 minutes.

Ingestion

Do NOT induce vomiting. Do not use mouth-to-mouth method if victim ingested the substance. Get medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

 If material is ingested and aspirated into the lungs it may cause chemical pneumonitis. Treat appropriately.

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media •

LARGE FIRE: Water spray, fog or regular foam. SMALL FIRES: Dry chemical, CO2, water spray or regular foam.

Unsuitable Extinguishing Media

No data available.

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

Heat builds up pressure in closed containers. Cool with water stream.
 Toxic fumes and vapors may be produced.

Hazardous Combustion Products

Carbon dioxide, carbon monoxide, acrid smoke, irritating fumes.

5.3 Advice for firefighters

 Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

Wear positive pressure self-contained breathing apparatus (SCBA). Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection. Runoff from fire control may cause pollution.

LARGE FIRES: Dike fire-control water for later disposal.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

 Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate enclosed areas.

Emergency Procedures

 As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area) Stay upwind. Keep out of low areas. Keep unauthorized personnel away. Ventilate closed spaces before entering.

6.2 Environmental precautions

Avoid run off to waterways and sewers.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

 SMALL SPILLS: Take up with sand or other non-combustible absorbent material and place into containers for later disposal.
 Use clean non-sparking tools to collect absorbed material.
 All equipment used when handling the product must be grounded.
 LARGE SPILLS: Dike far ahead of spill for later disposal.
 A vapor suppressing foam may be used to reduce vapors.

6.4 Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

Keep away from heat, sparks, and flame – No Smoking. Keep containers closed. Vapors of this material are heavier than air and will collect in low or confined areas. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations near container. Static electricity may accumulate and create a fire hazard. Take precautionary measures against static charges. Bond and ground all transfer containers and equipment. Use only with adequate ventilation. Do not breathe (dust, vapor or spray mist) Ground fixed equipment.

7.2 Conditions for safe storage, including any incompatibilities

Storage

 Store in a cool/low-temperature, well-ventilated place away from heat and ignition sources. Store locked up. Keep container closed when not in use. Keep away from incompatible materials.

7.3 Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines

No exposure limits/guidelines available for the material or the components.

			Ex	posure Limits	s/Gu	idelines			
	Result	ACGIH	Ca	anada Ontario	С	anada Quebec	China	NIOSH	
Calcium oxide	STELs	Not established	Not e	established	Not	established	5 mg/m3 STEL	Not established	
(1305-78-8)	TWAs	2 mg/m3 TWA	2 mg	ı/m3 TWA	2 m	g/m3 TWAEV	2 mg/m3 TWA	2 mg/m3 TWA	
	STELs	Not established	Not e	established	Not	established	8 mg/m3 STEL (total dust)	Not established	
Carbon Black (1333-86-4)	TWAs	3 mg/m3 TWA (inhalable fraction)	3.5 n	ng/m3 TWA	3.5	mg/m3 TWAEV	4 mg/m3 TWA (total dust)	3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as PAH)	
Bentonite	STELs	Not established	Not 6	established	Not established		12 mg/m3 STEL (total dust)	Not established	
(1302-78-9)	TWAs	Not established	Not 6	established	Not established		6 mg/m3 TWA (total dust)	Not established	
	STELs	Not established	Not 6	established	Not established		16 mg/m3 STEL (total dust); 8 mg/m3 STEL (respirable dust)	Not established	
Limestone (1317-65-3)	TWAs	Not established	Not 6	Not established		ng/m3 TWAEV nestone, taining no estos and <1% stalline silica, total t)	8 mg/m3 TWA (total dust); 4 mg/m3 TWA (respirable dust)	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)	
		Ex	cpos	ure Limits/Gu	idel	ines (Con't.)			
				Result		OSHA			
Calcium oxide (1305-78-8)			TWAs		5 mg/m3 TWA				
Carbon Black (1333-86-4)				TWAs		3.5 mg/m3 TWA			
Limestone			TWAs		15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)				

Exposure Control Notations

ACGIH

•Carbon Black (1333-86-4): Carcinogens: (A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans)

Exposure Limits Supplemental

ACGIH

- •Calcium oxide (1305-78-8): TLV Basis Critical Effects: (upper respiratory tract irritation)
- •Carbon Black (1333-86-4): TLV Basis Critical Effects: (bronchitis)

8.2 Exposure controls

Engineering Measures/Controls Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values.

Personal Protective Equipment









Respiratory

• In case of insufficient ventilation, wear suitable respiratory equipment. Follow the

OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Safety glasses with side shields should be worn at a minimum.

- Wear appropriate gloves.
- Wear nitrile or polyvinyl alcohol gloves for direct handling.
- Follow best practice for site management and disposal of waste. Avoid release to the environment.

Eye/Face Hands Skin/Body

Environmental Exposure Controls

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Black paste with characteristic aliphatic solvent naphtha odor.
Color	Black	Odor	Characteristic aliphatic solvent naphtha odor.
Odor Threshold	Data lacking		
General Properties			
Boiling Point	115.6 C(240.08 F)	Melting Point	Data lacking
Decomposition Temperature	Data lacking	рН	Data lacking
Specific Gravity/Relative Density	1.35 Water=1	Water Solubility	Negligible < 0.1
Viscosity	Data lacking	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
Volatility			
Vapor Pressure	45 mmHg (torr) @ 20 C(68 F)	Vapor Density	3.8 Air=1
Evaporation Rate	9.2 n-Butyl Acetate = 1		
Flammability			
Flash Point	10 C(50 F) TCC (Tagliabue Closed Cup)	UEL	6.7 %
LEL	.9 %	Autoignition	Data lacking
Flammability (solid, gas)	Data lacking		
Environmental			
Octanol/Water Partition coefficient	Data lacking		

9.2 Other Information

No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4 Conditions to avoid

 Avoid flames, sparks, or other sources of ignition. Excess heat. Incompatible materials.

10.5 Incompatible materials

Acids, alkalies, strong oxidizers.

10.6 Hazardous decomposition products

• Hazardous decomposition will not occur.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Component Name	CAS	Data
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) (< 5%)	64742-52-5	Irritation: skn-rbt 500 mg SEV
Carbon Black (< 1.5%)	1333-86-4	Acute Toxicity: orl-rat LD50:>15400 mg/kg; skn-rbt LD50:>3 gm/kg; Tumorigen/Carcinogen: ihl-rat TCLo:11600 ug/m3/18H/2Y-l

GHS Properties	Classification
Acute toxicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Aspiration Hazard	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Carcinogenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Germ Cell Mutagenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Skin corrosion/Irritation	EU/CLP • Skin Irritation 2 OSHA HCS 2012 • Skin Irritation 2
Skin sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
STOT-RE	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
STOT-SE	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
Toxicity for Reproduction	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Serious eye damage/Irritation	EU/CLP • Classification criteria not met OSHA HCS 2012 • Eye Irritation 2

Potential Health Effects Inhalation

Acute (Immediate)

• May cause respiratory irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.

Chronic (Delayed)

No data available.

Skin

Acute (Immediate)

Causes skin irritation.

Chronic (Delayed)

No data available.

Eye

Acute (Immediate)

Causes serious eye irritation.

Chronic (Delayed)

No data available.

Ingestion

Acute (Immediate)

Ingestion of this product unlikely.

Chronic (Delayed)

No data available.

Carcinogenic Effects

 This product contains carbon black (encapsulated)(1333-86-4). According to IARC "No significant exposure to carbon black is thought to occur during the use of products in which carbon black is bound to other materials, such as rubber, printing ink or paint."

		Carcinogenic Effects
	CAS	IARC
Carbon Black	1333-86-4	Group 2B-Possible Carcinogen

Section 12 - Ecological Information

12.1 Toxicity

 This material may be toxic to aquatic organisms and cause long-term adverse effects in the aquatic environment.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in Soil

No data available.

12.5 Results of PBT and vPvB assessment

No PBT and vPvB assessment has been conducted by the manufacturer.

12.6 Other adverse effects

Potential Environmental Effects

May cause long lasting harmful effects to aquatic life.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

Containers, even those that have been emptied, can contain explosive vapors. Dispose
of content and/or container in accordance with local, regional, national, and/or
international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1133	Adhesives	3	III	NDA
TDG	UN1133	ADHESIVES	3	II	NDA
IMO/IMDG	UN1133	ADHESIVES	3	II	NDA
ADN	UN1133	ADHESIVES containing flammable liquid (vapour pressure at 50 °C not more than 110 kPa)	3	II	NDA
ADR/RID	UN1133	Adhesives	3	II	NDA
IATA/ICAO	UN1133	Adhesives	3	II	NDA

14.6 Special precautions for user

None known.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Fire

	State Right To Know							
Component	CAS	MA	NJ	PA				
Limestone	1317-65-3	Yes	Yes	Yes				
Light aliphatic solvent naphtha	64742-89-8	No	No	No				
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	No	No	No				
Bentonite	1302-78-9	No	No	No				
Carbon Black	1333-86-4	Yes	Yes	Yes				
Calcium oxide	1305-78-8	Yes	Yes	Yes				

	Inventory							
Component	CAS	Canada DSL	Canada NDSL	China	EU EINECS	EU ELNICS		
Limestone	1317-65-3	No	Yes	Yes	Yes	No		
Light aliphatic solvent naphtha	64742-89-8	Yes	No	Yes	Yes	No		
Hydrotreated heavy naphthenic								

distillates (petroleum) (Highly Refined)	64742-52-	5 Yes	No	Yes	Yes	No
Bentonite	1302-78-9	Yes	No	Yes	Yes	No
Carbon Black	1333-86-4	Yes	No	Yes	Yes	Yes
Calcium oxide	1305-78-8	Yes	No	Yes	Yes	No
			Inventory (Co	n't.)		
Component		CAS	Japan ENCS	Korea KECL	1	rsca
Limestone	13	317-65-3	Yes	Yes		Yes
Light aliphatic solvent naphtha	64	4742-89-8	No	Yes		Yes
Hydrotreated heavy naphthenic distillate (petroleum) (Highly Refined)	26	4742-52-5	Yes	Yes		Yes
Bentonite	13	302-78-9	No	Yes		Yes
Carbon Black	13	333-86-4	Yes	Yes		Yes

Yes

Yes

C

Calcium oxide

1305-78-8

abor Canada - WHMIS - Classifications of Substar	ices					
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs)		< 5%	Not Listed			
Calcium oxide	1305-78-8	< 1%	Е			
			D2A (In certain cases,	this classificati	on does not ap	ply. Fo
Carbon Black	1333-86-4	< 1.5%	more information, cons Issues - Carbon Black, WHMIS Division websit	non-respirable		
Limestone	1317-65-3	30% TO 60%		- /		
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	B2			
Bentonite	1302-78-9	< 1.5%	D2A			
Canada - WHMIS - Ingredient Disclosure List						
Hydrotreated heavy naphthenic distillates (petro	leum) (Highly F	Refined)		64742-52-5	< 5%	Not Listed
 Hydrotreated heavy naphthenic distillates (petro of 15 polynuclear aromatic hydrocarbons (PAHs) 	leum) (Highly R	Refined) as Oil r	nist, mineral, sum total		< 5%	Not Listed
Calcium oxide				1305-78-8	< 1%	1 %
Carbon Black				1333-86-4	< 1.5%	1 %
Limestone				1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha				64742-89-8	10% TO 30%	Not

Yes

• Bentonite 1302-78-9 < 1.5% Not Listed

Environment Canada - CEPA - Priority Substances List			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
• Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed

Denmark

Denmark - List of Undesirable Substances - Product Groups/Function			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs)		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
• Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
• Bentonite	1302-78-9	< 1.5%	Not Listed

Europe

Other EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Carc.Cat.2; R45
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed

Carbon Black Limestone	1333-86-4 1317-65-3	< 1.5%	Not Listed	
Light aliphatic solvent naphtha	64742-89-8	10% TO 3	Carc.Cat.	2; R45
Bentonite	1302-78-9	< 1.5%	Muta.Cat.2	2; R46 Xn; R65
	1002 70 0	1.070	TVOT Elotoc	•
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits				
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)		64742	2-52-5 < 5%	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mir of 15 polynuclear aromatic hydrocarbons (PAHs)	neral, sum tot	tal	< 5%	Not Listed
Calcium oxide		1305-	-78-8 < 1%	Not Listed
Carbon Black		1333-	-86-4 < 1.5%	Not Listed
Limestone		1317-	-65-3 30% T	O 60% Not Listed
Light aliphatic solvent naphtha		64742	2-89-8 10% T	Listea
Bentonite		1302-	78-9 < 1.5%	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling				
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	6	4742-52-5	< 5%	T R:45 S:53-45
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mir total of 15 polynuclear aromatic hydrocarbons (PAHs) 	neral, sum		< 5%	Not Listed
Calcium oxide		305-78-8	< 1%	Not Listed
Carbon Black Limestone		333-86-4 317-65-3	< 1.5% 30% TO 60%	
Light aliphatic solvent naphtha	6	4742-89-8	10% TO 30%	T R:45-46-65 S:53-45
Bentonite	1	302-78-9	< 1.5%	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparation	ons			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)		6474	2-52-5 < 5%	L
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, min polynuclear aromatic hydrocarbons (PAHs) 	neral, sum to	tal of	< 5%	Not Listed
Calcium oxide		1305	i-78-8 < 1%	Not Listed
Carbon Black		1333	-86-4 < 1.5%	Listed
Limestone		1317	7-65-3 30% T	O 60% Not Listed
Light aliphatic solvent naphtha		6474	2-89-8 10% T	
Bentonite		1302	-78-9 < 1.5%	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases				

 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 	64742-52-5	< 5% < 5%	S:53-45 Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	S:53-45
Bentonite	1302-78-9	< 1.5%	Not Listed

Mexico

Mexico				
Other Mexico - Hazard Classifications				
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed	
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 		< 5%	Not Listed	
Calcium oxide	1305-78-8	< 1%	Hazard Cla = III UN1910	
Carbon Black	1333-86-4	< 1.5%	Not Listed	
Limestone	1317-65-3	30% TO 60%	Not Listed	
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed	
Bentonite	1302-78-9	< 1.5%	Not Listed	
Mexico - Regulated Substances				
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)		64742-52-5	< 5%	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, minera of 15 polynuclear aromatic hydrocarbons (PAHs) 	l, sum total		< 5%	Not Listed
Calcium oxide		1305-78-8	< 1%	UN1910
Carbon Black		1333-86-4	< 1.5%	Not Listed
Limestone		1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha		64742-89-8	10% TO 30%	Not Listed
Bentonite		1302-78-9	< 1.5%	Not Listed

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs)		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
• Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed
U.S OSHA - Specifically Regulated Chemicals			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs)		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
• Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Light dilphatic solvent haphtina			Not

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Lhidrateastad hagan garbthagia distillatas (astrolaura) (Highly Dafinad)	04740 50 5	- F0/	Not
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total 	64742-52-5	< 5%	Listed Not
of 15 polynuclear aromatic hydrocarbons (PAHs)		< 5%	Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
• Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed
U.S CERCLA/SARA - Radionuclides and Their Reportable Quantities			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs)		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
• Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs)		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
• Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed

- Hydratroated heavy paphthonic distillates (natroloum) (Highly Refined) as Oil mist, mineral oum total			Not
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 		< 5%	Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
• Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed
U.S CERCLA/SARA - Section 313 - Emission Reporting			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed
U.S CERCLA/SARA - Section 313 - PBT Chemical Listing			
			NI-4
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed

United States - California

Environment
U.S. - California - Proposition 65 - Carcinogens List

Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742 52 5	< 5%	Not Listed		
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) 	04742-02-0	\ 3 /0	NOT LISTED		
as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs)		< 5%	Not Listed		
Calcium oxide	1305-78-8	< 1%	Not Listed		
Carbon Black	1333-86-4	< 1.5%	carcinogen, initi (airborne, unbo		
- Galbon black	1000-00-4	1.570	respirable size)	and particles o	
• Limestone	1317-65-3	30% TO 60%			
Light aliphatic solvent naphtha Pontonite	64742-89-8	10% TO 30%			
Bentonite	1302-78-9	< 1.5%	Not Listed		
U.S California - Proposition 65 - Developmental Toxicity					
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)			64742-52-5	< 5%	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) a of 15 polynuclear aromatic hydrocarbons (PAHs) 	as Oil mist, mir	neral, sum total		< 5%	Not Listed
Calcium oxide			1305-78-8	< 1%	Not Listed
Carbon Black			1333-86-4	< 1.5%	Not Listed
Limestone			1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha			64742-89-8	10% TO 30%	Not Listed
Bentonite			1302-78-9	< 1.5%	Not Listed
U.S California - Proposition 65 - Maximum Allowable Dose Leve	els (MADL)				
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)			64742-52-5	< 5%	Not Listed
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) a of 15 polynuclear aromatic hydrocarbons (PAHs)	as Oil mist, mir	neral, sum total		< 5%	Not Listed
Calcium oxide			1305-78-8	< 1%	Not
					Listed Not
Carbon Black			1333-86-4	< 1.5%	Listed
Limestone			1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha			64742-89-8	10% TO 30%	Not Listed
Bentonite			1302-78-9	< 1.5%	Not Listed
U.S California - Proposition 65 - No Significant Risk Levels (NSR	L)				
• Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)			64742-52-5	< 5%	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) a of 15 polynuclear aromatic hydrocarbons (PAHs) 	as Oil mist, mir	neral, sum total		< 5%	Not Listed

Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Female			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Male			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
• Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed

United States - Pennsylvania

Labor
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
Limestone	1317-65-3	30% TO 60%	Not Listed
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed
U.S Pennsylvania - RTK (Right to Know) - Special Hazardous Substances			
Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined)	64742-52-5	< 5%	Not Listed
 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 		< 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Not Listed
Carbon Black	1333-86-4	< 1.5%	Not Listed
Carbon Black Limestone	1333-86-4 1317-65-3	< 1.5% 30% TO 60%	
			Listed Not
• Limestone	1317-65-3	30% TO 60%	Listed Not Listed Not

United States - Rhode Island

Labor U.S. - Rhode Island - Hazardous Substance List

 Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) Hydrotreated heavy naphthenic distillates (petroleum) (Highly Refined) as Oil mist, mineral, sum total of 15 polynuclear aromatic hydrocarbons (PAHs) 	64742-52-5	< 5% < 5%	Not Listed
Calcium oxide	1305-78-8	< 1%	Toxic; Flammable
Carbon Black	1333-86-4	< 1.5%	Toxic
Limestone	1317-65-3	30% TO 60%	Toxic
Light aliphatic solvent naphtha	64742-89-8	10% TO 30%	Not Listed
Bentonite	1302-78-9	< 1.5%	Not Listed

15.2 Chemical Safety Assessment

 No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

Section 16 - Other Information

Last Revision Date Preparation Date Disclaimer/Statement of Liability

- 15/April/2013
- 18/April/2012
- The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.

Key to abbreviations NDA = No Data Available