

QuickPrime Plus

1. Description

Firestone QuickPrime Plus is designed to clean and prime the PondGard™ membrane in seaming areas, before application of a QuickSeam product. The primer activates the PondGard™ membrane surface and improves the seam quality. Firestone QuickPrime Plus must be applied with a QuickScrubber.

2. Preparation

Surfaces that will receive QuickPrime Plus must be clean, smooth, dry and free of sharp edges, loose materials, oil, grease and other contaminants. The mating surface of the PondGard membrane shall be cleaned with a brush or clean rag. Stir the primer before and during use to achieve a uniform mix with no sediment on the bottom and no marbling evident. Restore the primer to room temperature prior to use if exposed to cold temperatures (< 15°C).



3. Application

Apply QuickPrime Plus to the Firestone PondGard membrane surfaces with the QuickScrubber tool using long back and forth strokes with moderate to heavy pressure along the length of the area until surfaces become dark grey in color with no streaking or puddling. Allow the primed surfaces to dry completely (usually less than 10 minutes) before applying the QuickSeam product.

4. Coverage

Coverage rate of ± 10 m², both sides, or ± 60 lin.m. of standard 3" seam per gallon. Thinning is not allowed.

5. Characteristics

| | |
|------------------|---|
| Physical | <ul style="list-style-type: none"> Resists temperature shocks up to 100°C Excellent resistance to ageing, heat and cold Translucent when dry which allows guide marks to show through after application |
| Technical | <ul style="list-style-type: none"> Base: rubber polymers Color: translucent grey Solvents: heptane, toluene, methyl alcohol Solids (%): 16-18 Viscosity (cP): Very thin, free flowing Specific gravity: 0.793 Flash Point (°C): < -18 |

6. Precautions

Store in original unopened carton at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

Shelf life is expected to be 12 months, when stored in above-mentioned conditions. Shelf life information is only a recommendation and not a fact of life. The actual expiration date depends on the history of storage and handling of the product. Quality and applicability should thus always be verified: when mixed, product should stir into a smooth and homogeneous blend with no evidence of major clumping or separation/phasing. Once opened, use within 48 hours.

Verify production date on the pail. Shelf life will be reduced if exposed to higher temperatures.

Refer to Safety Data Sheets. For professional use only. Flammable. Keep away from fire and open flame and other possible ignition sources during storage and use. Do not smoke when using. Use only in well ventilated areas. Avoid prolonged contact with skin. Keep out of reach from children.