

## QuickSeam Splice Tape

### 1. Description

Firestone QuickSeam Splice Tape is a 76 mm wide (3") adhesive strip designed for field splicing of Firestone PondGard™ membrane panels.

### 2. Preparation

The PondGard™ membrane surfaces must be prepared with QuickPrime Plus, using a QuickScrubber tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

### 3. Application

Refer to splicing section for specific installation instructions. Use of Firestone QuickPrime Plus and QuickScrubber is required.

### 4. Coverage

In accordance with length of detail.

### 5. In accordance with length of detail.

The Firestone QuickSeam Splice Tape is a rubber material with the following properties:

<b>Physical</b>	<ul style="list-style-type: none"><li>• Excellent moisture resistance</li><li>• Excellent resistance to heat and cold, U.V. radiation and ozone</li><li>• Contact with some kind of oils, petroleum products, hot bitumen and grease must be avoided</li></ul>
<b>Technical</b>	<ul style="list-style-type: none"><li>• Base rubber polymers</li><li>• Color black</li><li>• Solvents none</li><li>• Solids (%) 100</li><li>• State cured</li></ul>

### 6. Precautions

Take care when moving, transporting or handling to avoid sources of punctures and physical damage. Isolate waste products, such as petroleum products, greases, oils (mineral and vegetable) and animal fats from Firestone QuickSeam Splice Tape.

Store in original unopened carton at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

Shelf life is expected to be 12 months, when stored in above-mentioned conditions. Verify production date on each roll. Shelf life will be reduced if exposed to higher temperatures.

